



DESCRIPTION:

The Rockdrill Oil range has been formulated and blended with Group II virgin base oils, supported with extreme pressure additive technology, corrosion inhibitors, anti-foam, anti-oxidation and good emulsification characteristics, needed in pneumatically powered rock drilling machines.

APPLICATION:

Rockdrill Oil range is recommended for use in pneumatic rock drills and other air tools. Applications include tunnelling, bolting, deep hole drilling, drilling and blasting, and hand held air-leg and multi-boom jumbos.

FEATURES AND ADVANTAGES:

- Good load carrying ability.
- outstanding anti-wear, rust and corrosion protection.
- minimum carbon deposits.
- excellent high temperature oxidation stability.
- superior or excellent lubricity at low temperature.
- exceptional emulsification characteristics.
- impressive water-separating characteristics.

PHYSICAL PROPERTIES:

SAE	100	150	220
VISCOSITY @ 40 °C	100 cST	150 cST	220 cST
VISCOSITY @ 100 °C	10,76 cST	14,11 cST	18,6 cST
FLASH POINT (PMCC)	246 °C	249 °C	272 °C
POUR POINT	-9 °C	-9 °C	-12 °C
VISCOSITY INDEX	96	95	95
WATER CRACKLE	NIL		

PRODUCT ICON:



DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:
TECHNICAL ADVICE LINE (C. WRIGHT):
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD
(+27) 82 071 9560
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.