



DESCRIPTION:

Slideway Oils are specially formulated and blended multi-functional oils containing carefully selected friction controlling agents together with extreme pressure, anti-oxidant, anti-wear, anti-corrosion, anti-foam and tackiness additives. Formulated using virgin Group II (synthetic technology) base oils to combine the anti-stick-slip, adhesive and protection properties of a slide way lubricant with the anti-wear properties of modern hydraulic oil. Their dual-purpose nature enables the user to rationalize machine shop lubricants.

APPLICATION:

Slide Way Oils are particularly suitable for machine tools with combined slideway lubrication/hydraulic systems and can be used in old and new systems and applied either by centralized systems or by hand. These features, together with their suitability for machine tool headstocks and aprons, minimize the possibility of cross contamination. It is also suitable in other industrial applications requiring tacky, non-corrosive product with EP properties.

FEATURES AND ADVANTAGES:

- Smooth, chatter-free operation.
- Accurate table positioning.
- Rust and corrosion inhibitor protects machine components.
- Stays in place.


PERFORMANCE LEVEL:

- Cincinnati P47/ P 50/P53
- GM-LS-2

PHYSICAL PROPERTIES:

ISO	68	220
VISCOSITY @ 40°C	68 cST	220 cST
VISCOSITY @ 100°C	8.6 cST	19,5 cST
VISCOSITY INDEX	108	103
POUR POINT	-33°C	-30°C

PRODUCT ICON:



DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:
TECHNICAL ADVICE LINE (C. WRIGHT):
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD
(+27) 82 071 9560
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.