



### DESCRIPTION:

Super Two Stroke Plus is a cutting edge, non-ash forming Two Stroke SAE 30 Motor Oil. Using virgin Group II (synthetic technology) base oils and the latest additive packs it provides excellent fluidity and miscibility characteristics - meeting requirements set for Grade 2 of SAE J1536 and exceeds API TC performance levels. For ease of identification, it is dyed blue.

### APPLICATION:

Super Two Stroke Plus can be used in applications where it is premixed with the fuel, alternatively where metered injection into the engine intake system is at ratios up to 50:1. Always use the ratio recommended by the OEM. Especially formulated for modern air cooled two stroke petrol engines but also suited to racing and severe duty two stroke motorcycle engines, as well as modern high revving chainsaws, lawnmowers, scooters, and generator sets.

### FEATURES AND ADVANTAGES:

- Exceeds API TC
- Extended spark plug life
- Protection against spark plug fouling
- Effective lubrication at all speeds and loads
- Excellent fluidity and miscibility characteristics
- Protection against combustion chamber and exhaust port deposits

### PERFORMANCE LEVEL:

- API TC, SAE J1536 Grade 2

### PHYSICAL PROPERTIES:

VISCOSITY @ 40 °C	68cST
VISCOSITY @ 100 °C	9,6cST
FLASH POINT PMCC	110
POUR POINT	-9
VISCOSITY INDEX	110
COLOUR	BLUE

### PRODUCT ICON:



#### DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

#### HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:  
TECHNICAL ADVICE LINE (C. WRIGHT):  
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD  
(+27) 82 071 9560  
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.