

DESCRIPTION:

Transmission Fluid DX-III is a high-quality automatic transmission fluid formulated using virgin quality Group II base oils including multifunctional additives with viscosity index improvers, anti-wear agents, detergents and dispersants plus red dye. It is suitable to give universal performance for extended periods of operation. It also provides the controlled frictional characteristics specifically required to meet Allison C4 requirements.

APPLICATION:

Recommended for use in automatic transmissions. Can be used in off-highway transmissions, power steering and other hydraulic applications.

FEATURES AND ADVANTAGES:


- Excellent lubrication at all operating temperatures, even at temperatures below -40° C.
- Protection against wear & corrosion.
- Correct frictional properties for each type of automatic transmission.
- Better performance as a result of foam resistance.
- Protection against deposit formation.

PERFORMANCE LEVEL:

- Dexron (registered) IID* General Motors
- Mercon (registered) Ford Motors
- Mercedes Benz Sheet 236
- Caterpillar TO-2
- HAGGLUNDS Denison HF-O
- ZF TE -ML 09, ZF TE -ML 11, ZF TE -ML 14
- Sperry Vickers hydraulic pump system

PHYSICAL PROPERTIES:

VISCOSITY @ 40°C	39.15 cSt
VISCOSITY @ 100°C	8.083 cSt
VISCOSITY INDEX	186
DENSITY @ 20°C	0.8480
FLASH POINT (PMCC)	>200° C

PRODUCT ICON:**DISCLAIMER AND GENERAL ADVICE**

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:
TECHNICAL ADVICE LINE (C. WRIGHT):
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD
(+27) 82 071 9560
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.