

DESCRIPTION:

Transmission Fluid ATF DX-II is a high-quality automatic transmission fluid formulated from virgin Group II (synthetic technology) base oils and a High Viscosity Index additive technology pack, combining viscosity index improvers, anti-oxidants, anti-wear agents, detergents, dispersants and special additives to provide the controlled frictional characteristics required to meet the requirements of automatic transmissions.

APPLICATION:

Transmission Fluid DX-II is used in car and light truck automatic transmissions. On and off-highway heavy-duty automatic transmission. Power steering systems.

FEATURES AND ADVANTAGES:


- Excellent lubrication at all operating temperatures.
- Protection against wear & corrosion.
- Correct frictional properties for each type of automatic transmission.
- Better performance as a result of foam resistance.
- Protection against deposit formation.

PERFORMANCE LEVEL:

- Caterpillar TO-2
- Voith
- ZF TE –ML 09, ZF TE –ML 11, ZF TE –ML 14
- Dexron II
- Sunstrand

PHYSICAL PROPERTIES:

VISCOSITY @ 40°C	38 cSt
VISCOSITY @ 100°C	7.9 cSt
VISCOSITY INDEX	170
POUR POINT	-45 °C
DENSITY @ 20°	0.870
FLASH POINT (PMCC)	155 °C
APPEARANCE	RED FLUID

PRODUCT ICON:**DISCLAIMER AND GENERAL ADVICE**

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:
TECHNICAL ADVICE LINE (C. WRIGHT):
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD
(+27) 82 071 9560
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.