



### DESCRIPTION:

Triton Enduradrive 10W40 is a (SPDO) quality engine oil meeting the latest ACEA E7 and API CI-4 approvals for Turbo Diesel Engines, available in a shear stable viscosity SAE 10W40. Blended from high-quality virgin Group II (synthetic technology) base oils and supported with the latest cutting edge multifunctional additive packs, it provides excellent anti-wear protection, resistance to bore polishing and superior engine cleanliness, and may be used with confidence in mixed American and European fleets both on and off the road.

Triton Enduradrive 10W40 has been formulated for extended oil drain up to 100 000km in modern European diesel engines in accordance with OEM specifications. However, it is recommended to follow drain intervals provided by South African OEM's due to the quality of South African diesel fuels.

### APPLICATION:

Triton Enduradrive 10W40 is recommended for heavy-duty automotive diesel engines operating in severe service conditions such as high-output direct-injection, turbocharged engines. It is particularly recommended for use in EGR and other advanced technology engines developed to reduce emissions.

This product can also be used in gasoline engines which call for the API-SL Classification.

### FEATURES AND ADVANTAGES:

- Improved engine life and reduced service costs due to its superior protection.
- Excellent levels of engine cleanliness are maintained and valve and piston deposits are controlled.
- Optimum engine reliability and operational economy.
- Advanced anti-wear technology provides protection against valve train wear.
- Excellent TBN retention throughout the service life of the oil.
- Conservation of energy through lowered drag and reduced fuel consumption.

### PERFORMANCE LEVEL:

- API CI-4/SL
- Cummins CES 20077/78
- Deutz DQC III-10
- Mack EO-M Plus / EO-N
- MAN M3277
- Renault Truck RLD-2 / RXD
- ACEA E4/E7-16
- DDC 93K215
- Global DHD-1
- MB 228.5
- MTU Type 3
- Volvo VDS-3

#### DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

#### HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:  
TECHNICAL ADVICE LINE (C. WRIGHT):  
CUSTOMER SERVICE:

DEOJAY PETROLEUM (PTY) LTD  
(+27) 82 071 9560  
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM (PTY) LTD AND ARE USED UNDER LICENSE.



### PHYSICAL PROPERTIES:

VISCOSITY @ 40 °C	100 cSt
VISCOSITY @ 100 °C	14.5 cSt
VISCOSITY INDEX	150
POUR POINT	-27 °C
DENSITY @ 20 °C	0.885
SULPHATED ASH (% MAX)	1.5
TBN	11.4

### PRODUCT ICON:



#### DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

#### HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:  
TECHNICAL ADVICE LINE (C. WRIGHT):  
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD  
(+27) 82 071 9560  
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.