

DESCRIPTION:

Deojay's premium Universal Farm Oil is a 15W40 multigrade which has been engineered and designed primarily for use in both normally aspirated and turbo charged diesel engines, as well as most transmissions and hydraulic systems found on modern agriculture implements. This product is formulated with virgin Group II (synthetic technology) base oils and high-performance internationally formulated additive technology to meet industry needs.

APPLICATION:

Universal Farm Oil can be used in transmissions, hydraulic systems, final drives, power steering systems and fluid immersed disc brakes in agricultural and industrial tractors and other similar equipment

FEATURES AND ADVANTAGES:

- One oil for the farm.
- Excellent anti-squawk properties.
- Excellent rust and corrosion protection.
- High oxidation stability protect against the formation of gums and varnish.
- Outstanding control of low temperature sludge and deposits.

PERFORMANCE LEVEL:

- API CF-4/SF, API GL4, API GL5 (low speed high torque)
- Allison C-4
- Case IHMS 1207
- Caterpillar TO-2
- Ford ESN-M2C-159C & M2C134D
- Ford New Holland
- John Deere JDM J27, J20A & J20 C
- Massey Ferguson M-1127, M-1135, M-1139, M 1144
- Mercedes Benz 227.1
- MIL-L-2104D – CLMC D4

PHYSICAL PROPERTIES:

VISCOSITY @ 40°C	112 cSt
VISCOSITY @ 100°C	13 cSt
VISCOSITY INDEX	115
TBN	11
POUR POINT	-25°C
FLASH POINT (PMCC)	>200°C

PRODUCT ICON:



DISCLAIMER AND GENERAL ADVICE

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION. WHILST FUTURE PRODUCTION WILL CONFORM TO DEOJAY PETROLEUM KZN (PTY) LTD SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR. ALL REASONABLE CARE HAS BEEN TAKEN TO ENSURE THAT THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE AS AT THE TIME OF PRINTING, SOME INFORMATION IS NEVERTHELESS LIABLE TO VARIATION IN THE EVENT OF CHANGES TO ANY OF THE FOLLOWING OCCURRING SUBSEQUENT TO THE DATE OF PRINTING: THE BLEND FORMULATION, METHODS OF STORAGE, DUE TO THE IMPROPER HANDLING OR APPLICATION OF ANY OF THE PRODUCTS REFERRED TO, OR REQUIREMENTS OF ANY SPECIFICATION OR APPROVAL RELATING TO ANY OF THE PRODUCTS.

HEALTH AND SAFETY

GUIDANCE ON HEALTH AND SAFETY ARE AVAILABLE ON THE APPROPRIATE MATERIAL SAFETY DATA SHEET, WHICH CAN BE OBTAINED FROM YOUR DEOJAY REPRESENTATIVE.

FOR MORE INFORMATION CONTACT:
TECHNICAL ADVICE LINE (C. WRIGHT):
CUSTOMER SERVICE:

DEOJAY PETROLEUM KZN (PTY) LTD
(+27) 82 071 9560
(+27) 31 569 1276

THE DEOJAY NAME AND DEOJAY LOGO ARE TRADEMARKS OF DEOJAY PETROLEUM KZN (PTY) LTD AND ARE USED UNDER LICENSE.